

ISA™ OR+™ Multigas Monitoring

Supporting Anesthetic Agent and Ventilation Management



The ISA OR+ sidestream multigas analyzer with the Masimo Root® patient monitoring and connectivity platform provides the following features and benefits:

- > During general anesthesia, the ISA OR+ monitors the inhaled and exhaled concentration of five anesthetic gas agents (Sevoflurane, Isoflurane, Halothane, Desflurane, Enflurane), carbon dioxide (CO₂), nitrous oxide (N₂O), and oxygen (O₂), in addition to respiration rate
- > Requires only 50 ml sampling flow to support monitoring
- > Time-saving in critical situations with virtually no warm-up time and full accuracy performance in less than 20 seconds
- > Automatic anesthetic agent identification
- > Supports monitoring patients with high respiration rates, up to 150 bpm
- > Low-power consumption and automatic temperature and pressure compensation
- > Provides minimal alveolar concentration (MAC) calculated from the measured anesthetic agents and N₂O*
- > Appropriate for monitoring adult, pediatric, or infant patients in a range of clinical environments including the operating room and intensive care unit
- > Compatible with Masimo's Nomoline™ Adapter and the Nomoline Airway Adapter Set to interface with endotracheal tubing

COMPONENTS



MOC-9 Ports on Root



Single-patient-use Nomoline Airway Adapter Set



Nomoline Adapter

The portable ISA OR+ module easily mounts onto the back of Root and plugs into a MOC-9™ Port



ISA OR+ MOC-9 Module

When technology modules are connected with Root, multiple additional parameters are available including Masimo SET® pulse oximetry, noninvasive and continuous hemoglobin (SpHb®), PVI®, SedLine® brain function monitoring, and O3™ Regional Oximetry (not available for sale in the U.S.)

PERFORMANCE AND SPECIFICATIONS

GENERAL	GAS ANALYZER
Weight..... < 420 g	Automatic compensation Pressure, temperature, and broadening effects on CO ₂
Size..... 49 x 90 x 100 mm (1.9 x 3.5 x 3.9 inches)	Warm-up time..... < 20 sec
Power Supply..... 4.5 to 5.5 VDC < 2.0 W (normal op.)	ISA sampling flow rate..... 50 ± 10 ml/min
ENVIRONMENTAL	Fulfills the requirements of EN ISO 80601-2-55:2011.
Operating temperature 5 to 50 °C (41 to 122 °F)	Accuracy during standard conditions:
Storage -40 to 70 °C (-40 to 158 °F)	
Operating humidity < 4 kPa H ₂ O (non-condensing) (95 %RH at 30 °C)	
Operating atmospheric pressure 525 – 1200 hPa (< 5211 m)	
PATIENT CONNECTIONS	
Nomoline See separate Nomoline information for full details of available options	
	RANGE
	ACCURACY
	CO ₂ 0 – 15 vol% ± (0.2 vol% + 2% of reading)
	N ₂ O 0 – 100 vol% ± (2 vol% + 2% of reading)
	HAL, ISO, ENF 0 – 8 vol% ± (0.15 vol% + 5% of reading)
	SEV 0 – 10 vol% ± (0.15 vol% + 5% of reading)
	DES 0 – 22 vol% ± (0.15 vol% + 5% of reading)
	O ₂ 0 – 100 vol% ± (1 vol% + 2% of reading)
	Rise time CO ₂ ≤ 250 ms, N ₂ O, Agents ≤ 350 ms, O ₂ ≤ 450 ms
	Total system response time < 3 sec
	Breath detect Adaptive threshold, minimum 1 vol% CO ₂ change
	Respiratory rate 0 – 150 bpm ± 1 bpm
	CERTIFICATIONS
	CE Marked according to the 93/42/EEC Medical Device Directive
	Data subject to change without notice

* Altitude, patient age and other individual factors are not considered in the MAC calculation.

Caution: Federal law restricts this device to sale by or on the order of a physician.

For professional use. See instructions for use for full prescribing information, including indications, contraindications, warnings, precautions, and adverse events.